

China

CMC

COA

sih4

US \$45/kg Cylinder/Tank

15 days

50000kg/month

# Electronic Industrial Grade silicon source Cylinder Gas sih4 Silane

### **Basic Information**

- Place of Origin:
- Brand Name:
- Certification:
- Model Number:
- Minimum Order Quantity: 1kg
- Price:
  - · Packaging Details:
  - Delivery Time:
  - Payment Terms: L/C, T/T, Western Union
  - Supply Ability:



## **Product Specification**

- Product Name:
- Valve:
- Appearance:
- Melting Point:
- Cylinder Pressure:
- Cylinder Standard:
- Specification:
- Trademark:
- Origin:
- HS Code:
- Supply Ability:
- CAS No.:

- 12.5MPa/15MPa/20MPa
- Transport Package:

- Formula:

- Colorless, Garlic Smell -185 ºC

Silane Gas

Diss632

- GB/ISO/DOT
  - Y-Cylinder, T-Drum, T-Cylinder, T-Drum, Tt, Tanker
    - 20L, 40L, 280L And Customizable
    - CMC
    - Suzhou, China
    - 2812190091
    - 50000kg/Month
    - 7803-62-5
    - Sih4



#### More Images



Our Product Introduction

## **Product Description**

Silane gas, also known as monosilane (SiH4), is a colorless, flammable gas with a distinct odor. It consists of one silicon atom bonded to four hydrogen atoms and belongs to the group of silanes, which are compounds containing silicon and hydrogen. Silane gas is primarily used in various industries, including semiconductor manufacturing, solar cell production, and as a precursor in the deposition of thin films. It is often employed as a silicon source in the production of amorphous and crystalline silicon coatings. Silane gas is also utilized in the fabrication of optical fibers, as a reducing agent in metallurgy, and as a dopant in the production of electronic components.

Due to its flammability and reactivity, silane gas requires careful handling and storage. It is highly pyrophoric, meaning it can ignite spontaneously in the presence of air or other oxidizing agents. Safety measures, such as specialized equipment, proper ventilation, and strict protocols, are necessary when working with silane gas to prevent accidents and ensure worker safety.

#### Basic Info.

Model NO. Density Cylinder Pressure Specification HS Code Sih4 1.34 Kg/M<sup>3</sup> 12.5MPa/15MPa/20MPa 47L/440L/ISO Tank 2931900090 Boiling Point Melting Point Transport Package Origin Production Capacity

-112 °C -185 °C 47L/440L/ISO Tank China 20, 000tons/Year

#### Specification:

CAS No.: 7803-62-5 EINECS No.: 232-263-4 UN No.: UN2203 Purity: 99.9999% Dot Class: 2.1 Appearance: Colorless Grade Standard: Electronic Grade

Specification	99.9999%
Carbon Monoxide	≤ 0.05 ppm
Carbon Dioxide	≤ 0.05 ppm
Total chloride	≤ 0.1 ppm
Methane	≤ 0.05 ppm
C2-C4	≤ 0.1 ppm
Nitrogen	≤ 0.5 ppm
Oxygen	≤ 0.05 ppm
Moisture	≤ 0.1 ppm
Silyl Ether	≤ 0.1 ppm
Methyl Silane	≤ 0.1 ppm
Disilane	≤ 0.3 ppm
Hydrogen	≤ 20 ppm
Aluminum	≤ 0.02 ppba
Antimony	≤ 0.02 ppba
Arsenic	≤ 0.02 ppba
Gallium	≤ 0.02 ppba
Boron	≤ 0.02 ppba
Phosphorus	≤ 0.02 ppba
Iron + Chromium + Nickel + Copper + Zinc $\leq 1$ ppba	

#### **Detailed Photo**



Shanghai Kemike Chemical Co., Ltd is staffed by trained personnel, combine many years experience in Gas industry .We supply cylinder gas, electronic gas, etc., and the gas holder, panel, valves and fittings and other equipment, parts and engineering services to our customers in China and worldwide; The products are involved in various industrial fields, such as semiconductor chip, solar cell, LED, TFT-LCD, optical fiber, glass, laser, medicine, etc., Our mission is to partner with our global customers to provide support, solutions and quality products that are innovative, reliable, and safe. Our products mainly include: H2, O2, N2, Ar, CO2, propane, acetylene, helium, laser mixed gas, SiH4, Sih2cl2, SiHCL3, SiCL4, NH3, CF4, NF3, SF6, HCL, N2O, doping mixed gas (TMB, PH3, B2H6) and other electronic gases.

