



Cylinder Gas Helium Used In Cryogenics Welding Applications

Our Product Introduction

for more products please visit us on gascylindertank.com

Basic Information

- Place of Origin: China
- Brand Name: CMC
- Certification: COA
- Model Number: He
- Minimum Order Quantity: 1 Piece
- Price: US \$300/PC
- Packaging Details: Cylinder/Tank
- Delivery Time: 15 days
- Payment Terms: L/C, T/T
- Supply Ability: 3000 Pcs/Month



Product Specification

- Product Name: Helium Gas
- Purity: 99.9%-99.999%
- Formular: He
- Appearance: Colorless Gas
- Filling Pressure: 150 Bar-200 Bar
- Transport Package: He Cylinder
- Specification: 40L, 47L, 50L
- Trademark: CMC
- Origin: China
- HS Code: 28042900
- CAS No.: 7440-59-7
- Formula: He
- EINECS: 231-168-5
- Constituent: Industrial Pure Air
- Grade Standard: Industrial Grade



More Images



Product Description

Cylinder gas used in cryogenics welding applications Helium

Helium gas is a chemical element with the symbol He and atomic number 2. It is the second lightest and second most abundant element in the universe. Here are some key points about helium gas:

Chemical Symbol: He

Atomic Number: 2

Atomic Weight: 4.0026 g/mol

Physical Properties: Helium is a colorless, odorless, and tasteless gas at standard conditions. It is the least dense gas and has a lower density than air. Helium has a boiling point of -268.93 degrees Celsius (-452.07 degrees Fahrenheit) and a melting point of -272.2 degrees Celsius (-457.96 degrees Fahrenheit).

Abundance and Occurrence: Helium is the second most abundant element in the universe after hydrogen. However, it is relatively scarce on Earth. It is primarily obtained from natural gas deposits where it accumulates as a result of radioactive decay. Helium is often extracted during natural gas production.

Applications: Helium gas has various applications in different fields. One of its most well-known uses is for filling balloons and airships due to its low density and non-flammability. Helium is also used in cryogenics for cooling superconducting magnets in magnetic resonance imaging (MRI) machines and other scientific equipment. It is utilized in welding applications, as a shielding gas to prevent oxidation of metal during the welding process. Helium is also used in certain breathing mixtures for deep-sea diving and as a carrier gas in gas chromatography.

Liquid Helium: Helium can exist as a liquid at extremely low temperatures. Liquid helium is used in research laboratories for cooling superconducting materials, studying low-temperature physics, and operating superconducting magnets.

Helium-3 and Helium-4: Helium has two stable isotopes, helium-3 and helium-4. Helium-4 is the most common isotope, accounting for more than 99.9% of naturally occurring helium. Helium-3 is much rarer and has unique properties that make it useful in certain scientific and medical applications, such as neutron detection and nuclear magnetic resonance (NMR) spectroscopy.

Safety Considerations: Helium gas is generally considered to be non-toxic and does not pose any significant health hazards. However, as with any gas, inhaling excessive amounts of helium can lead to asphyxiation due to the displacement of oxygen in the air.

Conservation: Helium is a non-renewable resource, and its availability is limited. Due to its importance in various scientific, medical, and industrial applications, there have been efforts to conserve and recycle helium to ensure its availability for future use.

Basic Info.

DOT Class	2.2	Un Number	1963
Cylinder Standard	DOT/ISO/GB	Cylinder Pressure	15MPa/20MPa
Valve	Qf-2/Cga580	Melting Point	-272.2 °C
Appearance	Colorless, Odorless	Boiling Point	-272.2 °C
Density	0.1786 Kg/M3	Molecular Weight	4.0026
Transport Package	40L, 47L, 50L	Specification	99.999%, 99.9999%
Trademark	CMC	Origin	Suzhou, China
HS Code	28042900	Production Capacity	20,000 Tons/Yea



Specification:

Specification Company Standard

He	≥ 99.999%
N2	≤ 2.0 ppm
O2+AR	≤ 1.0 ppm
H2	≤ 1.0 ppm
CO	≤ 0.5 ppm
CO2	≤ 0.5 ppm
Ne	≤ 1.0 ppm
CH4	≤ 0.5 ppm
Moisture	≤ 0.5 ppm

Company Profile



Shanghai Kemike Chemical Co., Ltd is staffed by trained personnel, combine many years experience in Gas industry .We supply cylinder gas, electronic gas, etc ., and the gas holder, panel, valves and fittings and other equipment, parts and engineering services to our customers in China and worldwide; The products are involved in various industrial fields, such as semiconductor chip, solar cell, LED, TFT-LCD, optical fiber, glass, laser, medicine , etc., Our mission is to partner with our global customers to provide support, solutions and quality products that are innovative, reliable, and safe. Our products mainly include: H2, O2, N2, Ar, CO2, propane, acetylene, helium, laser mixed gas, SiH4, SiH2Cl2, SiHCl3, SiCl4, NH3, CF4, NF3, SF6, HCL, N2O, doping mixed gas (TMB, PH3, B2H6) and other electronic gases.

SiCl4	NH3	NH3	CH3F	SiH4	Kr	H2S	WF6	F6+Cl2
4MS	C3F8	C3F8	TEOS	CH4	PH3	SF6	C2	HCl+Ne
CF4	C4F8	SiH2						TMB+H2
SiF4	C3H8	Cl2						He +As
BBr3	C3H6	DCE						Ge+Se
POCl3	N2	SO2						D+B
BCl3	D2	CO2						CO+NO
SiHCl3	CH2F2	HF						Ar+O2
TMAI	DMZn	DEZn						Xe+NO
AsH3	C2H4	C2H2	HBr	COS	Ar+O2			
GeH4	C2H6	B2H6	H2Se	GeCl4	Xe+NO			



 **Shanghai Kemike Chemical Co.,Ltd**

 +86 18762990415

 williamchen@cmc-chemical.com

 gascylindertank.com